\ge CP PLUS

CP-GPC-LD24L3

2.4MP Full Color Guard+ Dome Camera

- 1/3" 2.4MP PS CMOS Image Sensor (0.84667cm)
- Max 25/30fps@2.4MP
- DWDR, 3D-NR, AWB, AGC
- 3.6mm Lens
- Illumination Range up to 30Mtrs., IP66
- Support OSD Menu





System Overview

Analog cameras can be advantageous in more ways than one – they are economical, especially for large scale setups, and are simple to install. However, one of the major downsides of earlier analog cameras was the image quality, which is critical in the present times. With subsequent technological upgrades over the years, HD resolution was introduced in analog CCTV systems. This served as a major breakthrough as high quality imagery was only available in IP system which was comparatively a costlier option. Another challenge with analog systems was its compatibility constraint. Newer versions of analog cameras would not pair up with older versions. CP PLUS introduced the revolutionary UNI+ technology which supported all analog & HD video formats including CVBS.



×CP PLUS



CP-GPC-LD24L3 2.4MP Full Color Guard+ Dome Camera

Functions

OSD Menu support

CP PLUS HD analog cameras come with their own menu using which the camera settings can be managed, for instance, the signal type can be changed and other sensor level adjustments be made.

Illumination Range

Numerous Illumination Range provide detailed images even in very low light conditions. These illumination range adjust the infrared intensity for distinct images in dark environments for up to 30mtrs.

UNI+ technology

CP PLUS Analog HD cameras offer compatibility across all the available technologies - TVI, HDCVI and AHD making upgrading simple and hassle-free.

Power protection

With a voltage tolerance range of ± 10 , these cameras are suitable even in fluctuating power conditions.

Plug & Play

CP PLUS Analog HD cameras are simple to configure and install.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



\ge CP PLUS



CP-GPC-LD24L3 2.4MP Full Color Guard+ Dome Camera

Feature	Specification
Image Sensor	1/3" 2.4MP PS CMOS Image Sensor (0.84667cm)
Minimum Illumination	Color : 0.01 lux@F2.0, 0 Lux with white light
Shutter Speed	Auto
Lens	3.6mm
Lens Type	Fixed
Focus Control	Fixed
Max. Aperture	F2.0
Whit Balance	Auto/ Manual
Noise Reduction	3D-NR
DWDR	Support
AGC	Auto
OSD Menu	Support
Video Streaming	2.4MP@25/30fps
Day/Night	Color
Illumination Distance	Illumination Range up to 30 Mtr.
Infrared LED	Support Warm white (4000K)
Casing	Plastic
Weatherproof Standard	IP66



Feature	Specification
Operating Temperature	-30°C ~ +50°C ; RH 95% max
Storage Temperature	-20°C ~ +60°C ; RH 95% max
Power Source	DC12V±10%, 450mA
Dimension	108mm x 85mm
Weight	400g

Company Name: CP PLUS (Aditya Infotech Ltd.) F-28 Okhla Industrial Area, Phase 1, New Delhi - 110020, INDIA Contact Mail ID :- customercare@cpplusworld.com

