

**CP- UNC-VD41L3E-VMD-J****4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.****Main Features**

- 1/3" 4Megapixel PS CMOS Image Sensor (0.84667cm)
- 25/30fps@4MP
- Instastream and H.264+ Triple -stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 3.6mm fixed lens (2.8mm optional)
- IR Range of 30 Mtrs, IP67, IK10, PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNC-VD41L3E-VMD-J

## 4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.

### Feature

Image Sensor  
Effective Pixel  
Minimum Illumination  
Shutter Speed  
Signal System  
White Balance  
Lens  
Gain Control (AGC)  
Video Compression  
S/N Ratio  
Back Light Compensation  
Angle of View  
Close Focus Distance  
Video Streaming  
Iris Type  
Image Rotation  
Motion detection  
Privacy Mask  
ICR  
ROI  
Audio Input  
Audio Output  
Audio Compression  
Alarm IN  
Alarm Out  
Alarm Event

### Specification

1/3" 4Megapixel progressive scan CMOS (0.84667cm)  
2560 × 1440, 4MP  
0.008 Lux @ F1.6  
Auto/Manual 1/3 s–1/100000 s  
PAL/NTSC  
Auto/Manual  
3.6mm (2.8mm optional)  
Auto/Manual  
Instastream; H.265; H.264+; H.264; H.264B; MJPEG  
>56dB  
BLC / HLC / WDR(120dB)  
3.6mm: Horizontal 84.0° × Vertical 45.0° × Diagonal 100.0°  
2.8mm: Horizontal 102.0° × Vertical 55.0° × Diagonal 121.0°  
2.8 mm: 0.9 m (2.95 ft) ; 3.6 mm: 1.6 m (5.25 ft)  
Main Stream: 4MP (2560×1440): Max. 25/30fps, (2688 × 1520) Max. 20fps  
Sub Stream1: 2MP (1920×1080): Max. 25/30 fps, Sub Stream 2 : D1(720×576): Max. 25/30fps  
Fixed  
0°/90°/180°/270° (Supports 90°/270° with 2688 ×1520 resolution and lower.)  
OFF/ON (4 areas, rectangular)  
4 Area  
Auto (ICR)/Color/B/W  
Support (4 areas)  
1 Ch.  
1 Ch.  
G.711a/ G.711Mu/ AAC/ G.726  
1 Ch.  
1 Ch.  
No SD card; SD card full; SD card error; network disconnection; IP conflict; motion detection; video tampering; tripwire; intrusion; illegal access; voltage detection; safety exception

# CP- UNC-VD41L3E-VMD-J

## 4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.

Feature	Specification
Bit Rate	H.264: 32 kbps–6144 kbps ;H.265: 12 kbps–6144 kbps
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour; ONVIF (Profile S/Profile G/Profile T); CGI; InstaOn; Milestone; Genetec
Smart Detection	Tripwire; intrusion
SDK and API	Support
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lock-out; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade
Ethernet	RJ-45 (10/100Base-T)
User Account	20 Users
Smart Phone	IOS, Android
IR	IR Range of 30 Mtr.
Micro SD	Micro SD Card, Max 256GB
Operating Temperature	-40°C to +60°C (-40°F to +140°F)/less than ≤ 95% RH
Power Source	12 V DC, PoE (802.3af)
Power Consumption	<5.2W
Weatherproof Standard	IP67 & IK10
Dimension	Φ109.9 x 81 mm (3.19" x Φ4.33")
Casing	Metal
Weight	0.350 kg