

CP- UNP-S3021L10-D**2MP 30x Explosion-proof IR Network PTZ Camera- 100 Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image sensor (0.9071 centimeters)
- Max. 50/60fps@1080P
- Powerful 30x Optical and 16x Digital zoom
- WDR(120dB), 2D/3D-DNR, Defog, EIS, Day/Night (ICR), AGC, BLC, HLC
- 316L Stainless Steel Housing
- Up to 256 presets, 5 Scan, 8 Tour
- IR Range of 100 Mtr.
- Max 40° /s pan speed, 360° endless pan rotation
- Built-in 2/1 alarm in/out, IP68
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNP-S3021L10-D

2MP 30x Explosion-proof IR Network PTZ Camera- 100 Mtr.

Feature

Image Sensor
 Effective Pixels
 Video Output
 S/N Ratio
 Minimum Illumination
 Focal Length
 White Balance
 Focus Control
 Close Focus Distance
 Angle of View
 AGC control
 Back Light Compensation
 Optical Zoom
 Digital Zoom
 Pan Travel
 Tilt Travel
 Manual Speed
 Presets
 Preset Speed
 Special Features
 Power up Action
 Idle Motion
 Day/Night: IR Cut Filter
 Video Compression
 Video Streaming
 Audio Compression
 Motion Detection
 ROI
 Audio Streaming
 Networking
 IVS

Specification

1/2.8" CMOS PS (0.9071 centimeters)
 1920(H) x 1080(V), 2 Megapixels
 1 Channel
 More than 55dB
 Color: 0.005Lux@F1.6; 0Lux@F1.6 (IR on)
 4.5mm~135mm
 Auto, ATW, Indoor, Outdoor, Manual
 Auto / Manual
 100mm~ 1000mm
 H: 67.8° ~ 2.4°
 Auto / Manual
 BLC / HLC / WDR(120dB)
 30x
 16x
 0°~360° endless, Pan Speed: 0.1° ~40° /s
 -90° ~ 90°, Tilt Speed: 0.1° ~40° /s
 Pan: 0.1° ~40° /s; Tilt: 0.1° ~40° /s
 256
 Pan: 40° /s; Tilt: 40° /s
 Defog, IR Range upto 100m, Up to 256 Presets, 5 Scan, 8 Tour
 Auto restore to previous PTZ and lens status after power failure
 Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
 Auto (ICR) / Color / B/W
 H.265/H.264
 Main stream: 1080P(1 ~ 50/60fps), 1.3MP/720P(1 ~ 25/30fps), Sub stream1: D1/CIF(1 ~ 25/30fps), Sub stream2: 1080P/1.3MP/720P(1 ~ 25/30fps)
 G.711a/G.711Mu/AAC/G.722/G.726/MPEG2-L2
 Supports
 Supports
 1/1 channel In/Out
 RJ-45 (10Base-T/100Base-TX) , 1 RS485
 Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map

CP- UNP-S3021L10-D

2MP 30x Explosion-proof IR Network PTZ Camera- 100 Mtr.

Feature

Protocols
Alarm
Max Remote Users
Operating Temperature
Smart Phone
Memory Slot
Weather Proof Standard
Dimension
Weight
Power Source
Power Consumption

Specification

IPv4/IPv6,HTTP,HTTPS,SSL,TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP,RTP, SMTP, NTP,DHCP, DNS,PPPOE,DDNS,FTP, IP Filter, QoS, Bonjour,802.1x, ONVIF, PSIA, CGI
2/1 channel In/Out
20 users
-40°C ~ 60°C (-40°F ~ +140°F) / Less than 95% RH
iPhone, iPad, Android Phone
Micro SD card 128GB
IP68
Φ482mm×393mm×295mm
28.9kg
AC220V(AC100V ~ 240V)
40W, 75W (IR on, Heater On)