

CP-UNR-4K632R8-EI

32Ch. 4K AI Network Video Recorder

- Up to 32 channel IP camera input
- Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth
- Instastream/H.265/Smart H.264+/H.264/MJPEG/MPEG4 codec decoding
- AI by NVR: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus
- Support 8 SATA HDDs up to 16TB Each, 4 USB Ports (2 USB 3.0)
- AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting
- Support RAID 0/1/5/6/10
- Supports N+M cluster
- Support Redundant Power Supply
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



System Overview

The CP Plus Series of NVRs have been meticulously designed for providing you with upgraded performance and higher recording quality in your IP video surveillance solution. The robust processor that has been inculcated in this NVR lets you enjoy 4K resolution and brings out every little detail from the picture in a clear view. This NVR is being used worldwide at a variety of places because of its easy-to-install design. This NVR also supports the features of open architecture that enable multi-user access and is also compatible with ONVIF 2.4 protocol which makes it interoperable with 4K cameras.

Functions

ANPR by Camera

The automatic number plate recognition technology is being widely used these days as this enables accurate, automatic reading of every vehicle's number plate that is crossing a border or an entrance and then automatically runs that number through the system to detect if the vehicle should be allowed to enter or not.



CP-UNR-4K632R8-EI

32Ch. 4K AI Network Video Recorder

Functions

Face Detection

With the help of the deep learning algorithm that is used in this technology, people can easily be detected, tracked, recorded, and captured. It takes only a second to detect one human face. Face detection is useful in cameras to help with auto-focus. This technology is mainly used to identify the presence of a human face.

Instastream

This camera has been designed with the latest and most efficient innovation among the standard video compression designs. Smart encoding algorithms developed by CP PLUS help in saving up to 70% more bandwidth than H.265 along with making it more beneficial for minimizing bandwidth and storage costs. It enhances video coding efficiency while providing high resolution and the rate of frame in the video using Intelligent Region Perception to detect motion in each frame.

Smart Motion Detection (SMD Plus)

CPPLUS has introduced Smart Motion Detection, AI-based SMD, which use an advanced algorithm to differentiate human and vehicular shapes within a scene and send alarms only when a person or vehicle is detected.

gCMOB/ iCMOB

Designed to allow users to access and control live streaming from CP PLUS IP Cameras, DVRs/ NVRs and Video Door Phones, the CP PLUS gCMOB/ iCMOB application offers a host of features such as Easy GUI, up to 16 live viewing split-ups; InstaOn cloud support; Playback; digital zoom ins; two-way talk, and more.

KVMS Pro

The KVMS Pro is a hybrid security management software that allows the management of various surveillance devices such as cameras, DVRs/ NVRs, encoders/ decoders, etc. It is released with the surveillance hardware and exclusively supports CP PLUS devices.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UNR-4K632R8-EI

32Ch. 4K AI Network Video Recorder

Feature	Specification
Processor	Industrial-grade processor
IP Camera Input	32 Channel
Operating System	Embedded LINUX
User Interface	Web, Local GUI
Video Output	2-channel VGA, 4-channel HDMI video output. Simultaneous mode: max. resolution of VGA1 and VGA2 is 1080p, max. resolution of HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Heterogeneous mode: Simultaneous video source output for VGA1 and HDMI1 Simultaneous video source output for VGA2 and HDMI2, max. resolution of VGA1 and VGA2 is 1080p, max. resolution of HDMI1, HDMI2 and HDMI3 is 4K, max. resolution of HDMI4 is 1080p
Compression	H.265; Smart H.264+; H.264; MPEG4; MJPEG
Encode Strategy	Instastream
Decoding Capability	2-channel 32 MP@30 fps; 2-channel 24 MP@30 fps; 4-channel 16 MP@30 fps; 8-channel 8 MP@30 fps; 16-channel 4 MP@30 fps; 32-channel 1080p@30 fps; 72-channel 720P@30 fps 160-channel D1@30fps
AI by NVR	Face detection; face recognition; video metadata (human, motor vehicles, and non-motor vehicles); SMD Plus
AI by Camera	Face detection; face recognition; video metadata (human, motor vehicles, and non-motor vehicles); SMD Plus; stereo analysis; crowd distribution; people counting; ANPR; vehicle density; object monitoring
Resolution	32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1
Network Bandwidth	AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing
Video Display Split	Main screen: 1/4/8/9/16/25/36 ; Sub screen: 1/4/8/9/16/25/36
Perimeter Performance AI by NVR (Number of Channels)	24 channels, 10 IVS rules for each channel

Feature	Specification
Perimeter Performance of AI by Camera (Number of Channels)	32 channels
Face Attributes	Gender; age group; glasses; expressions; face mask; beard
Face Detection Performance of AI by NVR (Number of Channels)	4 channels (up to 12 face images/s each channel)
Face Detection Performance of AI by Camera (Number of Channels)	32 channels
Face Database Capacity	Up to 40 face databases with 300,000 images, with a total capacity of 48 G. Name, gender, birthday, address, credential type, credential No., countries & regions and state can be added to each face image.
Face Recognition Performance of AI by NVR (Number of Channels)	<ol style="list-style-type: none"> 20 channels FD (by camera) + FR (by recorder), image stream: 20 face images/s 4 channels FD (by recorder) + FR (by recorder), video stream: 12 face images/s
Face Recognition Performance of AI by Camera (Number of Channels)	32 channels
SMD Plus by NVR	32-channel: Secondary filtering for human and motor vehicle , reducing false alarms caused by leaves, rain and lighting condition change
SMD Plus by Camera	32 channels
Metadata Performance of AI by NVR (Number of Channels)	8 channels
Metadata Performance of AI by Camera (Number of Channels)	32 channels
Human Attributes	Top color, top type, hat, bag, age, gender and umbrella
Motor Vehicle Attributes	License plate, plate color, vehicle model, vehicle logo, plate color, ornament, calling
Non-motor Vehicle Attributes	Vehicle model, vehicle color, number of persons, helmet
ANPR by Camera (Number of Channels)	32 channels

Feature	Specification
License Plate Database Capacity	Blocklist and allowlist: 20,000
Anomaly Alarm	Camera offline; storage error; disk full; IP conflict; MAC conflict; login lock; abnormal behaviour of fan
Intelligent Alarm	Face detection; face recognition; perimeter protection (intrusion and tripwire); SMD Plus alarms; ANPR; people counting; stereo analysis; crowd distribution; heat map
General Alarm	Motion detection; video tampering; video loss; scene changing, PIR alarm, IPC external alarm
Alarm Linkage	Record; snapshot; IPC external alarm output; buzzer; log, preset; email
Audio Input	1-channel RCA
Audio Output	2-channel RCA
Audio Compression	G.711a; G.711u; PCM; G726
Disk Group	Support
Alarm Input	16 channel
Alarm Output	8 channels
Hard Disk	8 SATA ports, up to 16TB each. The maximum HDD capacity varies with environment temperature
Multi-channel Playback	Up to 16 channels
Record Mode	Manual; alarm; motion detection; scheduled
Network Mode	Multi-address mode, load balance, fault tolerance and other network port binding modes
Backup Method	Portable hard drive, eSATA disk, burner, USB device and network
Playback Mode	<ol style="list-style-type: none"> 1. Play, pause, stop, fast forward, fast backward, rewind, play by frame 2. Full screen, backup (cut/file), partially enlarge, audio on/off
Smart Phone	iPhone, iPad, Android Phone
Hot Swapping	Support
RAID	RAID 0/1/5/6/10
Ethernet	2 (10/100/1000/2500 Mbps Ethernet port, RJ-45)

Feature	Specification
Interface Ports	4 (2 front USB 2.0 ports, 2 rear USB 3.0 ports), 4 HDMI, 2 VGA, 1 RS232, 1 RS485, 1 eSATA Port
Protocols	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; DDNS; Alarm Server; IP Search, Multicast; InstaOn cloud; Auto Registration; ISCSI, ONVIF (Profile T; Profile S; Profile G); CGI; SDK
Power Supply	100–240 VAC, 50-60 Hz
Redundant Power Supply	Support
Power Consumption	<18 W (without HDD)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–93% (RH)
Dimensions	444.0 mm × 476 mm x 95.0 mm (17.48" × 17.98" × 3.74") (W × D × H)
Weight	8.14 kg (without HDD)

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi - 110020, INDIA

Contact Mail ID :- customer@cpplusworld.com