

CP-UVR-0401E1-PG

4 Ch. H.265 Mobile Video Recorder

- Support 4 channels 1080P Realtime Recording
- Support H.265/Smart H.265 video compression
- Support Penta-Brid (HDCVI/AHD/TVI/CVBS/IP) video input
- Aviation connectors adopted
- Support 1 HDD and 1 SD card, 3 USB Ports (2.0)
- Support Face Detection
- VGA/TV simultaneous video output
- Micro SD card, Up to 256GB
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



System Overview

The CP PLUS Mobile Digital Video Recorder is perfect for any situation whether you are just starting your mobile surveillance and have an on-going sophisticated security operation. This MDVR is purposefully built for mobile environments with high-resolution recording as well as dual streaming technology. This MDVR comes with an enhanced system health monitoring solution that adds to your peace of mind by upholding the health level of your security system.

Functions

Multiple ports

With kinds of ports, like RS232, RS485, I/O, the video recorder can connect with various of accessories, such as card reader, fuel sensor, panic button and so on, so that the video, audio, alarm and location information can be uploaded to VMS.



CP-UVR-0401E1-PG

4 Ch. H.265 Mobile Video Recorder

Functions

GPS

This MDVR comes with an in-built GPS to support location tracking and relays the current location of the device in real-time to the control room.

Improved Management Capabilities

Flexible channel assignment, automatic IP addressing, dynamic camera configuration during alarm, and video management integration work together to simplify the system maintenance and management activities.

Vibration Resistant

This modern MDVR has been crafted with a vibration resistant design to prevent damage under harsh conditions or environmental pressures.

H.264 Video Compression

The most reliable video compression design, which is H.264, has been provided in this product. This technology is beneficial for minimising storage costs as well as enabling you to save on resolution and the rate of frame in the video with the help of Intelligent Region Perception to detect motion in each frame.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UVR-0401E1-PG

4 Ch. H.265 Mobile Video Recorder

Feature	Specification
Processor	Embedded microprocessor
Operating System	Embedded LINUX
Two-way Talk	1 channel Input, 1 channel Output
User Interface	GUI
Video Input	4 channels HDCVI/AHD/TVI/CVBS (Don't support audio in when connecting AHD/TVI cameras) + 4 channel 4MP IPC
Video Output	1 VGA, 2 TV
Compression	H.265/smart H.265 /H.264/smart H.264
Video Resolution	800×600
Resolution	4 ch@1080P Realtime Recording
Video Display Split	1/4/8/9
OSD	Channel name, time, GPS, license No
Privacy Masking	4 Rectangular zones (each camera)
Motion Detection	MD Zones:396(PAL:22×18,NT SC:22×15)
Video Loss	Supports
Audio Compression	G.711A/G.711U/PCM
Camera Blank	Supports
Alarm Input	9 channels,Alarm1–8 are local alarm input, Alarm 9 is pulse input.
Alarm Output	2 channels,1 relay out, 1 Controllable 12V out
Smart Phone	iPhone, iPad, Android Phone
Internal Hard Disk	1 SATA
SD Card	1 SD card, Up to 256 GB
Trigger Events	Recording, PTZ, Tour, Alarm, Email, FTP, Buzzer & Screen tips
Recording Mode	Manual, Schedule (Regular (Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, Motion Detection & Exact search (accurate to second)

Feature	Specification
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Playback	1 Channel
Backup Mode	USB Device/Network
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Interface Ports	3 USB 2.0, 2 Port RS232, 1 Port RS485, Heater (Optional)
Max User Account	128 users
3G	Built-in 3G/4G
GPS	Built-in high accurate GPS module (optional)
Ethernet	1 RJ-45 Port (10/100Mbps) and 1 6-pin aviation connector
Protocols	TCP/IP, UDP, DHCP, FTP, Email, Alarm Server
Power Supply	DC 6V~36V
Power Consumption	<8.4W (Without HDD)
Working Temp	-30°C (with heater)~ +70°C (-22°F ~ +158°F)
Working Humidity	10 ~ 90% RH
Dimensions	180mm×190mm×50mm
Weight	1.92Kg (without HDD)

Dimensions (mm/inch)

