

**CP- VNC-T41FR3-VMD****4 MP WDR Array Bullet Camera - 30Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP
- Ultra H.265, H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, Corridor Mode, Digital Defog, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Varifocal Lens
- IR Range of 30 Mtrs, Smart IR, Micro SD Card, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream**

# CP- VNC-T41FR3-VMD

## 4 MP WDR Array Bullet Camera - 30Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Angle of View  
 DORI Distance  
 Gain Control (AGC)  
 BLC  
 Video Compression  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Frame Rate  
 Privacy Mask  
 Video Output  
 ICR  
 ROI  
 Audio Input  
 Audio Output  
 Audio Compression  
 Audio  
 Alarm IN  
 Alarm Out  
 Dewarping  
 Protocol  
 Network Storage  
 Ethernet  
 IR

### Specification

1/3" 4MP Progressive scan CMOS  
 Colour: 0.005Lux (F1.4, AGC ON) 0Lux with IR on  
 Auto/Manual, 1~1/100000 s  
 Auto/Manual  
 2.8~12mm Varifocal Lens  
 91° ~ 27° (H), 54.4° ~ 13.7° (V), 118.3° ~ 33.2° (O)  
 2.8mm– 63 Detect (m) , 25.2 Observe (m), 12.6 Recognize (m), 6.3 Identify (m)  
 12mm– 270 Detect (m) , 108 Observe (m), 54 Recognize (m), 27Identify (m)  
 Auto/Manual  
 BLC/HLC/WDR(120dB)  
 Ultra H.265, H.265, H.264, MJPEG  
 >52dB  
 Triple  
 2592 × 1520  
 Main Stream: 4MP (2592x1520), Max 20fps; 4MP (2560x1440), Max 25fps; 3MP (2048x1520),  
 Max 30fps; Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x576), Max 30fps  
 Up to 8 areas  
 1 BNC, impedance 75Ω; amplitude 1V [p-p]  
 IR-cut filter with auto switch (ICR)  
 Up to 8 areas  
 impedance 35 kΩ; amplitude 2 V [p-p]  
 impedance 600 Ω; amplitude 2 V [p-p]  
 G.711  
 Two-way audio Supported  
 1 IN  
 1 Out  
 Support  
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,  
 UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS, ONVIF (Profile S, Profile G, Profile T), API  
 ANR, NAS(NFS)  
 1 RJ45 10M/100M Base-TX Ethernet  
 IR Range of 30 Mtr., Smart IR

# CP- VNC-T41FR3-VMD

## 4 MP WDR Array Bullet Camera - 30Mtr.

### Feature

OSD  
Micro SD  
Operating Temperature  
Humidity  
Casing  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

### Specification

Up to 8 OSDs  
Micro SD, up to 256GB  
-35°C ~ 60°C (-31°F ~ 140°F)  
≤ 95% RH (non-condensing)  
Metal  
DC 12V±25%, PoE (IEEE 802.3af)  
Max 9W  
IP67  
253.4mm x 86mm x 71.7 mm (9.98" x 3.4" x 2.8")  
1.0kg