

CP- VNC-T41ZR3-VMD**4 MP WDR Array Bullet Camera - 30Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP
- Ultra H.265, H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, Corridor Mode, Digital Defog, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Motorized Lens
- IR Range of 30 Mtrs, Smart IR, Micro SD Card, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream****CE FC** **RoHS**
COMPLIANT

CP- VNC-T41ZR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Angle of View
 DORI Distance
 Gain Control (AGC)
 BLC
 Video Compression
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 Video Output
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Audio
 Alarm IN
 Alarm Out
 Dewarping
 Protocol
 Network Storage
 Ethernet
 IR

Specification

1/3" 4MP Progressive scan CMOS
 Colour: 0.005Lux (F1.4, AGC ON) 0Lux with IR on
 Auto/Manual, 1~1/100000 s
 Auto/Manual
 2.8~12mm Motorized Lens
 91° ~ 27° (H), 54.4° ~ 13.7° (V), 118.3° ~ 33.2° (O)
 2.8mm– 63 Detect (m) , 25.2 Observe (m), 12.6 Recognize (m), 6.3 Identify (m)
 12mm– 270 Detect (m) , 108 Observe (m), 54 Recognize (m), 27Identify (m)
 Auto/Manual
 BLC/HLC/WDR(120dB)
 Ultra H.265, H.265, H.264, MJPEG
 >52dB
 Triple
 2592 × 1520
 Main Stream: 4MP (2592x1520), Max 20fps; 4MP (2560x1440), Max 25fps; 3MP (2048x1520), Max 30fps; Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x576), Max 30fps
 Up to 8 areas
 1 BNC, impedance 75Ω; amplitude 1V [p-p]
 IR-cut filter with auto switch (ICR)
 Up to 8 areas
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 Two-way audio Supported
 1 IN
 1 Out
 Support
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS, ONVIF (Profile S, Profile G, Profile T), API
 ANR, NAS(NFS)
 1 RJ45 10M/100M Base-TX Ethernet
 IR Range of 30 Mtr., Smart IR

CP- VNC-T41ZR3-VMD**4 MP WDR Array Bullet Camera - 30Mtr.****Feature**

OSD
Micro SD
Operating Temperature
Humidity
Casing
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

Up to 8 OSDs
Micro SD, up to 256GB
-35°C ~ 60°C (-31°F ~ 140°F)
≤ 95% RH (non-condensing)
Metal
DC 12V±25%, PoE (IEEE 802.3af)
Max 9W
IP67
253.4mm x 86mm x 71.7 mm (9.98" x 3.4" x 2.8")
1.0kg