

CP- VNR-3208**8 Ch. 4K Network Video Recorder****Main Features**

- 8 Channel IP Camera Input
- Ultra H.265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 8MP Recording
- 48 Mbps Incoming/Outgoing Bandwidth
- Support 2 SATA HDDs up to 10TB each, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3208

8 Ch. 4K Network Video Recorder

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 HDMI/VGA Output
 Compression
 Recording Resolution
 Live View/Playback
 Video Recording
 Video Display Split
 OSD
 Capability
 Audio Input
 Smart detection
 Audio Output
 Corridor Mode Screen
 Alarm Input
 Alarm Output
 Hard Disk
 ANR Technology
 Trigger Events
 Cloud Upgrade
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Max User Account

Specification

Dual-core embedded processor
 Embedded LINUX
 8 channel
 1 channel, RCA
 GUI
 HDMI, VGA , 4K(3840 x 2160)@30Hz, 1920 x 1080P@60Hz, 1920 x 1080P@50Hz, 1600 x 1200@60Hz, 1280 x 1024@60Hz, 1280 x 720@60Hz, 1024 x 768@60Hz
 Ultra H.265/H.265 / H.264
 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 48Mbps
 1/4/8/9
 Camera Title, Time, Motion Detection, Recording
 1 x 4K@30, 2 x 4MP@30, 3 x 3MP@25, 4 x 1080P@30, 8 x 720P@30
 1 channel, RCA
 Face Detection, Intrusion Detection, Cross Line Detection, Audio Detection, Defocus Detection, Scene Change Detection, Auto Tracking, Face Search, Behavior Search, People Counting
 1 channel, RCA
 3/4/5/7/9/10/12/16/32
 4 channel
 1 channel
 2 SATA ports, up to 10TB Each
 Supports
 Recording, PTZ, Alarm Out, Video Push, Email, Snapshot, Buzzer, etc
 Supports
 Time/Date, Alarm, MD, Exact Search (By Minute/Second)
 1/4/9/16
 USB, Network
 3 USB Port
 128

CP- VNR-3208**8 Ch. 4K Network Video Recorder****Feature**

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

Specification

1 RJ-45 10M/100M Self-adaptive Ethernet Interface

P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T

12V DC

≤ 5 W

-10°C ~ + 55°C (+14°F ~ +131°F)

10% ~ 90%

46mm x 315mm x 380mm (1.8" x 12.4" x 15.0")

≤ 2.18 Kg