

**CP- VNR-3232****32 Ch. 4K Network Video Recorder****Main Features**

- 32 Channel IP Camera Input
- Ultra H.265/ H.265/H.264 Video Formats
- Support 4K Resolution Upto 12MP Recording
- 320 Mbps Incoming/ 320Mbps Outgoing Bandwidth
- Support 2 SATA HDDs up to 10TB each, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



# CP- VNR-3232

## 32 Ch. 4K Network Video Recorder

### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 HDMI/VGA Output  
 Compression  
 Recording Resolution  
 Video Recording  
 Corridor mode screen  
 Capability  
 Live View/Playback  
 Video Display Split  
 Audio Input  
 Audio Output  
 Alarm Input  
 Alarm Output  
 Hard Disk  
 Playback  
 Interface Ports  
 Max User Account  
 Ethernet  
 Protocols  
 Power Supply  
 Power Consumption  
 Working Temp  
 Working Humidity  
 Dimensions  
 Weight

### Specification

Dual-core embedded processor  
 32 channel  
 Embedded LINUX  
 1 channel, RCA  
 GUI  
 HDMI: 4K (3840x2160) @60Hz, 4K (3840x2160) @30Hz, 1920x1080p @60Hz, 1920x1080p @50Hz, 1600x1200 @60Hz, 1280x1024 @60Hz, 1280x720 @60Hz, 1024x768 @60Hz  
 VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz  
 Ultra H.265/ H.265 / H.264  
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 320 Mbps  
 3/4/5/7/9/10/12/16 /32  
 2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30, 32 x D1  
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 1/4/8/9/16/32  
 1 channel, RCA  
 1 channel, RCA  
 8 channel  
 2 channel  
 2 SATA ports, up to 10TB Each  
 16 Channel  
 3 USB Port, 1 RS485  
 128  
 2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface  
 P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T  
 12V DC  
 ≤ 20 W  
 -10°C ~ + 55°C ( +14°F ~ +131°F )  
 10% ~ 90%  
 46mm × 315mm × 380mm ( 1.8" × 12.4" × 15.0" )  
 ≤ 2.48 Kg (without HDD)