

CP- UNC-DA21ZPL4-M

2MP Full HD IR Network Dome Camera - 40Mtr.



Main Features

- 1/2.7" 2MP PS CMOS Image Sensor (0.9407 centimeters)
- Max 25/30fps@ 2MP
- Instastream and H.264+ dual-stream encoding
- DWDR, Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8mm~12mm Motorized Lens
- IR Range of 40 Mtrs, IP67, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-DA21ZPL4-M

2MP Full HD IR Network Dome Camera - 40Mtr.

Feature

Image Sensor
 Minimum Illumination
 Effective Pixels
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Video Compression
 Back Light Compensation
 Angle of View
 Resolution
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Bit Rate
 Protocol
 Ethernet
 Event Trigger
 User/Host
 Smart Phone
 IR
 Micro SD
 Operating Temperature
 Power Source
 Power Consumption

Specification

1/2.7" 2Megapixel progressive CMOS (0.9407 centimeters)
 0.008 Lux@F1.7
 1920(H)x1080(V)
 Auto/Manual, 1/3~1/100000s
 Auto/natural/street lamp/outdoor/manual/regional custom
 2.8mm~12mm Motorized lens
 Auto/Manual
 Instastream/H.265/H.264+/H.264H/H.264B/ MJPEG
 BLC / HLC / DWDR
 Pan: 106°-33° Tilt: 56°-19° Diagonal: 127°-38°
 1080P (1920 × 1080); 1.3MP (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480);
 VGA (640× 480); CIF (352 × 288/352 × 240)
 Main Stream: 1920 × 1080 (1 fps-25/30 fps) Sub stream: 704 × 576 (1 fps-25 fps)
 704 × 480 (1 fps-30 fps)
 OFF/ON (4 areas, rectangular)
 4 areas
 Auto (ICR)/Color/B/W
 Yes (4 areas)
 H.264: 32 Kbps-6144 Kbps H.265: 12 Kbps-7424 Kbps
 IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast;
 ONVIF (Profile S); CGI; Genetec; InstaOn
 RJ-45 (10/100Base-T)
 Abnormality detection: no SD card, SD card full, SD card error, network disconnection, IP conflict,
 illegal access, Motion detection, video tampering, security exception
 6 Users
 iPhone, iPad, Android Phone
 IR Range of 40 Mtr., Smart IR
 FTP; Micro SD card (support max. 256 GB)
 -40°C to +60°C (-40°F to +140°F)/less than ≤ 95% RH
 DC12V, PoE (802.3af)
 < 6.3W

A large red diamond shape on the left side of the page, containing the text 'CP-'.

CP- UNC-DA21ZPL4-M

2MP Full HD IR Network Dome Camera - 40Mtr.

Feature

Weatherproof Standard

Casing

Dimension

Weight

Specification

IP67

Plastic

98.1 mm × Φ122 mm (3.9" × Φ4.8")

0.38 kg