

CP- UNC-TB21ZL6S-VMD**2MP Full HD WDR IR Network Bullet Camera - 60Mtr.****Main Features**

- 1/2.8\" 2MP Progressive Scan CMOS (7.112cm)
- Max. 25/30fps@2MP (1920×1080)
- H.265+ and H.264+ dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3DNR, ROI, AWB, AGC, BLC, HLC
- 2.7~13.5mm Motorized Lens
- IR Range of 60 Mtrs, Smart IR, Micro SD Card, IP67, IK10 (Optional), PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-TB21ZL6S-VMD

2MP Full HD WDR IR Network Bullet Camera - 60Mtr.



Feature

Image Sensor

Effective Pixels

Minimum Illumination

Shutter Speed

White Balance

Lens

Max. Aperture

DORI Distance

Angle of View

Gain Control (AGC)

Video Compression

Back Light Compensation

S/N Ratio

Video Streaming

Resolution

Digital Zoom

Motion detection

Privacy Mask

ICR

ROI

Audio Input

Audio Output

Audio Compression

Alarm IN

Alarm Out

Bit Rate

Protocol

Ethernet

Specification

1/2.8" 2MP PS CMOS (7.112cm)

1920(H)x1080(V)

0.006Lux/F1.4(Color,1/3s,30IRE) 0.05Lux/F1.4(Color,1/30s,30IRE) 0Lux/F1.4(IR on)

Auto/Manual, 1/3(4)~1/100000s

Auto/Natural/Street Lamp/Outdoor/Manual

2.7mm~13.5mm Motorized Lens

F1.4

W- 46m(Detect) 18m(Observe) 9m(Recognize) 5m(Identify)

T- 153m(Detect) 61m(Observe) 31m(Recognize) 15m(Identify)

H:106°~29°, V:57°~17°

Auto/Manual

H.265+/H.265/H.264+/H.264

BLC / HLC / WDR(120dB)

More than 50dB

Main Stream: 2MP (1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)

1080P(1920x1080)/SXGA(1280x1024)/1.3M(1280x 960)/720P(1280x720)/D1
(704x576/704x480)/VGA(640x480)/CIF(352x288/352x240)

16x

Off / On (4 Zone, Rectangle)

Off / On (4 Area, Rectangle)

Auto (ICR)/Color/B/W

Off / On (4 Zone)

1 channel In

1 channel Out

G.711A;G.711Mu;G.726;AAC

1 channel In: 5mA 5VDC

1 channel Out: 300mA 12VDC

H.265: 12K ~ 6400Kbps , H.264: 32K ~ 10240Kbps

HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP;DHCP ;DNS; DDNS; PPPOE; IPv4/v6; SNMP;
QoS; UPnP; NTP; ONVIF, PSIA, CGI

RJ-45 (10/100Base-T)



CP- UNC-TB21ZL6S-VMD

2MP Full HD WDR IR Network Bullet Camera - 60Mtr.



Feature

User Account

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Casing

Weatherproof Standard

Dimension

Weight

Specification

20 Users

iPhone, iPad, Android Phone

IR Range of 60 Mtr., Smart IR

Micro SD , Max 128GB

-30°C~+60°C , Less than 95%RH

DC12V, PoE (802.3af)

<11.4W

Metal

IP67, IK10 (Optional)

244.1mm×79mm×75.9mm (9.61"×3.11"×2.99")

1.08Kg