

**CP- VNC-D41R3-V2****4MP Full HD Array Dome Camera - 30Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max. 20fps@4MP
- Ultra 265, H.265, H.264, MJPEG Triple-stream Encoding
- DWDR, Day/Night (ICR), 2D/3D-DNR, ROI, Digital Defog, AWB, AGC, BLC, HLC
- 2.8mm lens (3.6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream****CE FC** **RoHS**  
COMPLIANT

# CP- VNC-D41R3-V2

## 4MP Full HD Array Dome Camera - 30Mtr.

### Feature

Image Sensor

Minimum Illumination

Shutter Speed

White Balance

Lens

DORI Distance

Gain Control (AGC)

S/N Ratio

Back Light Compensation

Angle of View

Video Compression

Video Streaming

Resolution

Frame Rate

Motion detection

Privacy Mask

ICR

ROI

Protocol

Ethernet

IR

OSD

Operating Temperature

Humidity

Weather Proof

Power Source

Power Consumption

Dimension

Weight

### Specification

1/3" 4MP Progressive scan CMOS

Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR

Auto/Manual, 1 ~ 1/100000s

Auto/Manual

2.8mm (3.6mm Optional)

2.8mm- 63 Detect (m) , 25.2 Observe (m), 12.6 Recognize (m), 6.3 Identify (m)

3.6mm- 90 Detect (m) , 36 Observe (m), 18 Recognize (m), 9 Identify (m)

Auto/Manual

>52 dB

BLC/ HLC/ DWDR

2.8mm - 104.4°(H) 54.4°(V) 135.7°(O) / 3.6mm - 78.9°(H) 39.6°(V) 97.0°(O)

Ultra 265,H.265, H.264, MJPEG

Triple

4MP

Main Stream: 4MP (2592 x 1520), Max 20fps; Sub Stream: 720P (1280 x 720), Max 20fps;

Third Stream: D1 (720 x 576), Max 20fps

Up to 4 areas

Up to 4 areas

IR-cut filter with auto switch (ICR)

Up to 2 areas

IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, ONVIF (Profile S, Profile T),API

10M/100M Base-TX Ethernet

IR Range of 30 Mtr.

Up to 4 OSDs

-30C ~ 60°C (-22°F ~ 140°F)

<95% RH (non-condensing)

IP67

12 V DC±25%, PoE (IEEE802.3 af)

Max 4W

Φ118 x 96 mm (Ø4.6" x 3.8")

0.35kg