

CP-VNC-V21FR3-VMD**2 MP WDR VF Array Vandal Dome Camera - 30Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- Ultra H.265, H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, Digital Defog, Corridor mode, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP67, IK10, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**Instastream****CE FC** **RoHS**
COMPLIANT

CP- VNC-V21FR3-VMD

2 MP WDR VF Array Vandal Dome Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 DORI Distance
 Gain Control (AGC)
 Angle of View
 Video Compression
 S/N Ratio
 Back Light Compensation
 Video Streaming
 Resolution
 Video Output
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Compression
 Audio Output
 Alarm IN
 Alarm Out
 Protocol
 Network Storage
 Ethernet
 IR
 OSD

Specification

1/2.8" 2MP Progressive scan CMOS
 Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR
 Auto/Manual, 1/~1/100000 s
 Auto/Manual
 2.8~12mm Varifocal Lens
 2.8mm- 45 Detect (m) , 18 Observe (m), 9 Recognize (m), 4.5 Identify (m)
 12mm- 192.9 Detect (m) , 77.1 Observe (m), 38.6 Recognize (m), 19.3 Identify (m)
 Auto/Manual
 94.0° ~28.0° (H), 56.7° ~ 14.4°(V), 122.2° ~ 34.4°(O)
 Ultra 265,H.265, H.264, MJPEG
 >52dB
 BLC/ HLC/WDR(120dB)
 Triple
 1920 × 1080
 1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
 Main Stream: 2MP (1920×1080): Max. 30 fps; Sub Stream: 2MP (1920×1080): Max. 30 fps;
 Third Stream: D1 (720×576): Max. 30 fps
 Up to 4 areas
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 8 areas
 impedance 35 kΩ; amplitude 2 V [p-p]
 G.711
 impedance 600 Ω; amplitude 2 V [p-p]
 1 IN
 1 Out
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,
 UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile G, Profile T), API
 ANR, NAS(NFS)
 1 RJ45 10M/100M Base-TX Ethernet
 IR Range of 30 Mtr., Smart IR
 Up to 8 OSDs

 **CP- VNC-V21FR3-VMD****2 MP WDR VF Array Vandal Dome Camera - 30Mtr.****Feature**

Micro SD
Audio
Operating Temperature
Humidity
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

Micro SD, up to 256GB
Two-way audio Supported
-40°C ~ +60°C (-40°F ~ 140°F)
≤ 95% RH (non-condensing)
DC12V±25%, PoE (IEEE802.3 af)
max. 7.2 W
IP67 & IK10
Φ148 x 111.3 mm (Ø5.8" x 4.4")
0.92 kg